



POLYCAR INDIA LIMITED

Industrial Cables LP No. 01/2019-20 Dtd : 25th May 2019

<p>POLYCAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</p>	<p>POLYCAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</p>
---	---

Size (sq.mm.)	FRLF						HR	
							FRLSH-LEAD FREE (GREEN WIRE)	
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	90 Mtrs.	Coils Per Box
0.75	395	48	785	28			825	28
1	515	36	1025	24	2050	12	1075	24
1.5	770	30	1535	16	3070	10	1610	16
2.5	1235	20	2465	12	4930	6	2590	12
4	1840	16	3680	8	7360	4	3865	8
6	2755	8	5510	6	11020	3	5785	6
10			9740	1				
16			15600	1				

<p>POLYCAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</p>	<p>POLYCAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</p>	<p>POLYCAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</p>
--	---	---

Size (sq.mm.)	FRLF		FRLS-H		FRZH/LSZH/HFFR		HR	
							FRLSH-LEAD FREE (GREEN WIRE)	
	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	180 Mtrs. (Pouch Packing)	Coils Per Box
0.75	2615	10	2745	10	2810	10		
1	3415	8	3585	8	3670	8	2150	12
1.5	5115	6	5370	6	5500	6	3220	10
2.5	8215	4	8625	4	8830	4	5180	6
4	8180	4	8590	4	8795	4	7730	4
6	12245	3	12860	3	13160	3	11570	3
10	21650	1	22730	1	23270	1		
16	34670	1	36400	1	37270	1		

Notes

- The above rates are exclusive of GST which shall be charged extra.
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.